

YUXIANG Home | About Us | Products | Production Line | Quality Control | Contact Us

Product Line



Sanitary Napkins Panty Liners Baby Diaper Adult Diapers Other Products PDF Catalogue











Product Line

>> Back

YX-WHD-600B Full-Automatic High-speed Vertical Fast-easy Packaging Sanitary Napkin Pad Machine



Function & Assemble Parts:

- 1. It can produce air-laid paper napkin pad, fluffy N. W fabric napkin pad and three pieces style napkin pad.(As per request, it can be added to produce cotton core napkin pad.) Products are in small fast-easy package.
- 2. It can be equipped with programmable controller to materialize auto controlling production procedure, embossment roller temperature, production speed and so on.
- 3. It can be equipped with touching screen controller and man-machine displayer.
- 4. During production, auto catch air-laid paper, N.W. fabric, perforated film and P.E. film. Auto control material tension and reject wasted products when catching material.
- 5. Auto set up alarm and stop machine during operation.
- 6. Main driving speed is regulated by frequency converter with high driving accuracy and auto rise & lower speed when feeding material.
- 7. Automatically correct the deviation of material during production. (Rectifier can be selected by customers themselves.)

Structure & Character:

- 1. Programmable controller, main drive frequency converter, man-machine interface and touching screen are of Japanese"Mitsubishi" brand.
- 2. During production, conveyance of material takes vacuum absorption to stable tension of material.
- 3. Positioning and molding procedure of products are equipped with electric differential device to conduct adjustment without stopping machine.
- 4. Driving system consists of gearwheel device, universal couplings and arc gear synchronous belt with good synchronization and high mechanical efficiency.
- 5. Driving components are installed on backboard of equipment to both facilitate adjustment and maintenance and protect the machine against the shake during production.
- 6. Bearing, conducting ring, pipe heater, synchronous belt and conveyance belt are of import brand.
- 7. Rolled material axle is in fast expanding style, which is reliable in usage.

Main Technical Parameter:

- 1. Designed Production speed: 1000PCS/min
- 2. Stadle Production speed: 700~800PCS/min
- 3. Machine power: 60 Kw (380V, 50Hz) (include glue applicator)
- 4. Overall size of equipment (L x W x H m): 13 x 2.2 x 2.1
- 5. Weight of equipment: about 12t

>> Back Sanitar